



NOTES

1. USE 8' POSTS FOR THE TYPE A DOUBLE RAIL END TREATMENT FROM POST A-A INCLUDING POST 3.
2. THE BOTTOM RAIL SHALL BE TUCKED BEHIND AND BOLTED TO POST A-A USING A $\frac{5}{8}$ " DIA. x $1\frac{1}{2}$ " LENGTH HEX. HEAD BOLT.
3. OFFSET BLOCKS ARE NOT REQUIRED FOR THE BOTTOM RAIL.
4. MAINTAIN HEIGHT OF TOP RAIL RELATIVE TO EDGE OF SHOULDER UNTIL A MAXIMUM HEIGHT OF 45" ABOVE GROUND IS REACHED.
5. THE SLOPE FILL MATERIAL SHALL BE COMPACTED FIRMLY TO THE ESTABLISHED X-SLOPE; STABILIZE
6. THE CONTRACTOR HAS THE OPTION TO CONSTRUCT THE END ANCHORAGE TERMINAL USING ONE OF THE FOLLOWING.
OPTION 1 - 4' STEEL POSTS (SEE STD. MD 605.01 & 605.01-02)
OPTION 2 - CONCRETE ANCHOR BLOCK (SEE STD. MD 605.01-03)
7. LOW SPEED INSTALLATIONS REQUIRE 50 FEET USING A 9:1 RATE.
8. PAID FOR PER LINEAR FOOT OF TRAFFIC BARRIER W BEAM (LENGTH DOUBLED) EXCEPT THE TYPE A END ANCHORAGE TERMINAL.

SPECIFICATION 605	CATEGORY CODE ITEMS										
APPROVED <i>Kirk G. McCall</i> DIRECTOR - OFFICE OF HIGHWAY DEVELOPMENT											
SHA State Highway Administration	<table> <tr> <td>APPROVAL • SHA REVISIONS</td><td>APPROVAL • FEDERAL HIGHWAY ADMINISTRATION</td></tr> <tr> <td>APPROVAL 11-10-99</td><td>APPROVAL 7-2-99</td></tr> <tr> <td>REVISED 2-10-04</td><td>REVISED 3-31-04</td></tr> <tr> <td>REVISED</td><td>REVISED</td></tr> <tr> <td>REVISED</td><td>REVISED</td></tr> </table>	APPROVAL • SHA REVISIONS	APPROVAL • FEDERAL HIGHWAY ADMINISTRATION	APPROVAL 11-10-99	APPROVAL 7-2-99	REVISED 2-10-04	REVISED 3-31-04	REVISED	REVISED	REVISED	REVISED
APPROVAL • SHA REVISIONS	APPROVAL • FEDERAL HIGHWAY ADMINISTRATION										
APPROVAL 11-10-99	APPROVAL 7-2-99										
REVISED 2-10-04	REVISED 3-31-04										
REVISED	REVISED										
REVISED	REVISED										

Maryland Department of Transportation STATE HIGHWAY ADMINISTRATION STANDARDS FOR HIGHWAYS AND INCIDENTAL STRUCTURES TYPE A TRAFFIC BARRIER END TREATMENT (DOUBLE RAIL)

STANDARD NO. MD 605.01-01